

PRODUCT BULLETIN

PURAFIL BATHROOM ODOR & AMMONIA BLEND

Purafil Custom Media Blends

Are you ready for a custom solution that eliminates the gases that activated carbon leaves behind? A one-size-fits-all solution won't cut it, which is why Purafil specially engineered custom blends to address the unique problems you face while permanently removing gases—even the ones carbon can't remove—from the air. This is done through chemisorption, which chemically transforms gases into harmless solids that remain trapped inside the media.

Bathroom Odor & Ammonia Blend

Our Bathroom Odor & Ammonia media blend specifically targets exhaust gases and odors from bathrooms and common cleaning compounds. This allows for a more effective removal of the gases and contaminants.

- Ideal for use in:
 - Commercial Buildings
 - Hospitals & Healthcare Facilities
 - Hotels & Casinos
 - Airports
 - Educational Institutions
- Available in:
 - Purafil High Efficiency (HE), V-Bank, Canisters, Modules, Boxes, Sling Bags
- Target Gases: H₂S, NH₃, -NH₂

Engineering Specifications

1.0 Media Performance

- 1.1 Shall be the proprietary Purafil® engineered media blend designed for Bathroom Odor & Ammonia removal
- 1.2 Engineered media shall use chemisorption process to chemically transform contaminant gases into inert solids trapped inside the media, removing gases permanently from the air, unlike activated carbon
- 1.3 Engineered media shall be rated to withstand a continuous operating temperature of up to 125°F
- 1.4 Engineered media shall come in a factory-sealed delivery device from Filtration Group
- 1.5 Media Life Analysis (MLA) shall be conducted to determine remaining usable life



APPLICATION GUIDELINES

Temperature	-4°F to 125°F (-20°C to 51°C)
Humidity	10 - 95% RH
Air Speed	60 - 500 fpm (0.30 - 2.54 m/s)
Performance	99.5% (min) initial removal efficiency in Purafil systems
Bulk Density	46 lb/ft ³ (0.74 g/cc) ±5%

Removal Capacity by Weight

